




# **Composer Scripting**



#### Hello!

# I am Kunal Kursija

- Mumbai, India
- Drupal Engineer @axelerant
- Twitter: @kunalkursija
- Drupal: <a href="https://www.drupal.org/u/kunalkursija">https://www.drupal.org/u/kunalkursija</a>
- LinkedIn: <a href="https://www.linkedin.com/in/kunalkursija/">https://www.linkedin.com/in/kunalkursija/</a>



# What is a script?

In Composer's terms, Script can either be a PHP-Callback(static methods only) or CLI commands.

# Where are scripts placed?

Scripts are defined at the root level of your composer.json.

```
"scripts": {
"key1": "value",
"key2": [
    "value1",
    "value2"
```

# **Composer Events**

Composer fires different events during its execution, Which allows other packages to hook into composer and perform certain tasks.

# **Categorising Events**

kunalkursija@kunals-MacBook-Pro composer install **Command Events Installer Events** Package Events **Plugin Events** 

#### **Event Classes**



#### **Command Events**

- pre-install-cmd: occurs before the install command is executed with a lock file present.
- post-install-cmd: occurs after the install command has been executed with a lock file present.
- pre-update-cmd: occurs before the update command is executed, or before the install command is executed without a lock file present.
- post-update-cmd: occurs after the update command has been executed, or after the install command has been executed without a lock file present.
- post-status-cmd: occurs after the status command has been executed.
- pre-archive-cmd: occurs before the archive command is executed.
- post-archive-cmd: occurs after the archive command has been executed.
- pre-autoload-dump: occurs before the autoloader is dumped, either during install / update, or via the dump-autoload command.
- post-autoload-dump: occurs after the autoloader has been dumped, either during install / update, or via the dump-autoload command.
- post-root-package-install: occurs after the root package has been installed, during the create-project command.
- post-create-project-cmd: occurs after the create-project command has been executed.



#### **Installer Events**

- pre-dependencies-solving: occurs before the dependencies are resolved.
- post-dependencies-solving: occurs after the dependencies have been resolved.

# **Package Events**

- pre-package-install: occurs before a package is installed.
- post-package-install: occurs after a package has been installed.
- pre-package-update: occurs before a package is updated.
- post-package-update: occurs after a package has been updated.
- pre-package-uninstall: occurs before a package is uninstalled.
- post-package-uninstall: occurs after a package has been uninstalled.

### **Plugin Events**

- init: occurs after a Composer instance is done being initialized.
- command: occurs before any Composer Command is executed on the CLI. It provides you with access to the input and output objects of the program.
- pre-file-download: occurs before files are downloaded and allows you to manipulate the RemoteFilesystem object prior to downloading files based on the URL to be downloaded.
- pre-command-run: occurs before a command is executed and allows you to manipulate the InputInterface object's options and arguments to tweak a command's behavior.

## **Demo**

Let's see events in action...

# **Writing & Executing Custom Composer Commands**

- Composer allows us to create & execute custom commands
- Executing PHP scripts
- Executing Shell scripts
- Executing Drush commands
- Executing Composer commands
- Script Referencing

## **Demo**

Let's see custom commands in action...

# Questions?

# Thank You!

